

DECLARATION OF PERFORMANCE

Nr. 2020/05

- 1. Unique identification code of the product : TOGO 30
- 2. Intended use: the product is used for thermal insulation. More information on page www.togoputos.lt
- 3. Manufacturer: JSC "Ekotogas" Kastonu ave. 6, Prusaliai, LT-90101 Plunges r.
- 4. System used to assess and verify the constancy of performance for this particular (construction) product: carried out in accordance with conformity assessment system 3
- 5. Harmonised standard: LST EN 14315 -1:2013 "Thermal insulation products for construction. Locally formed hard polyurethane (PUR) and polyisocysonicurate (PIR) foam products. PART 1: Specifications used for hard spray foam systems before installation".
- 6. Declared performance:

MAIN FEATURE	INDICATOR, CLASS LEVEL	TEST METHOD
Declared thermal conductivity factor	0,027W/m* k	EN12667
Flammability class	Е	EN13501
Close-cell foam content	CCC 3 Nuo > 80 % Iki 89 %	ISO 4590
Water vapour resistance factor, µ	20	EN12086
Soaked partially submerged	0,25 kg/m2	EN1609
Dimensional stability	DS (TH)3 Prie 70±2 C, 90 ±5 Ilgis +1.57 % Plotis +2.15 % Storis +5.2 %	EN1604
Gelling time	GT7(20) 7-9 s	EN14315-1
Formation of a creamy mass	CT5(20) 3-6 s	EN14315-1
Non-adhesion time	TFT9(20) 10-13 s	EN14315-1
Foam density	FRB 27-33 kg/m3	EN14315-1

Reliability of the provided product is correspondant to all declared performances. This declaration of performance is
made in compliance with Regulation (EU) No 305/2011. Responsibility of the content is limited to the manufacturer
specified in the document.